VLPT-52HT70U





5x2 HDMI/DP/USB-c Presenter HDBT 70m

The 5x2 Seamless Presentation Switcher provides 3×HDMI, 1×DP, and 1×USB-C (video only) inputs, 1×HDMI and 1×HDBaseT mirrored outputs with PIP/PAP/Tri/Quad-view Multiview functionality. It supports single-screen seamless switching with no freezing, black, or snow screen. One 3.5mm audio de-embedding jacket can output analog stereo audio. Use Front Buttons or RS232 commands to control the switcher.

Featured Highlights

- 5x2 presentation switcher with PIP/PAP/Tri/Quad-view
- True seamless switching, no freezing, black, or snow screen
- HDMI 2.0b, HDCP 2. 2, DP1.4 up to 4K60@4:4:4
- 3×HDMI, 1×DisplayPort and 1×USB-C inputs
- 1×HDMI, 1×Mirrored HDBaseT 70M/POC outputs
- Full screen/PIP/PAP/Tri/Quad-view 5 configurable display modes
- Up to 14 output resolutions are selectable
- 3.5mm analog audio de-embedding
- EDID management
- Buttons and RS-232 control







TECHNICAL SPECIFICATIONS		
HDMI Compliance	HDMI 2.0b	
HDCP Compliance	HDCP 2.2	
DP Compliance	DP 1.4	
Video Resolution	Up to 3840×2160@60Hz	
ESD Protection	Human-body Model: ±8kV (Air-gap discharge), ±4kV (Contact discharge)	

CONNECTIONS SPECIFICATIONS			
Switcher	INPUTS:	3×HDMI IN [Type A, 19-pin, Female] 1×DP IN 1×USB-C	
	OUTPUTS:	1×HDBaseT OUT [RJ45] 1×HDMI OUT [Type A, 19-pin, Female] 1×L/R OUT [3.5mm□mini-Jack]	
Receiver	INPUT: OUTPUT: 1:	1×HDBaseT In [RJ45] ×HDMI OUT [Type A, 19-pin Female]	

MECHANICAL SPECIFICATIONS		
Housing	Metal Enclosure	
Color	Black	
Dimensions	Switcher: $225mm(W) \times 100mm(D) \times 25mm(H)$ Receiver: $157mm(W) \times 90mm(D) \times 20mm(H)$	
Weight	Switcher: 750g; Receiver: 333g	
Power Supply	Input: AC100~240V 50/60Hz Output: DC 24V/1A	
Power Consumption	14W (Max)	
Operation Temperature	0°C ~ 40°C / 32°F ~ 104°F	
Relative Humidity	10~50% RH (non-condensing)	

Classic Application Example

