## **VLWC-USBC**





### **USB-C Dongle Transmitter**

VLWC-USBC is a USB-C dongle that work compliantly with all of our wireless media bases, unlike other dongle in the market to start casting with button click, it provides a different user experience with touch and tap, with is more easy and efficient; as same with HDMI dongle, it doesn't require installation of any software or driver, what's more? neither it needs additional USB power cable to connect, which gives more convenience to use.

#### **Featured Highlights**

- With popular USB-C interface
- APP-free
- Plug and play
- · Easy to use



# CS:VigilLink


## **VLWC-USBC**

TECHNICAL	
HDCP	HDCP1.3
Video Input Formats	Compliant with DP 1.2 for 1.62Gbps, 2.7Gbps ,5.4Gbps Compliant with DP 1.2 and eDP1.4 Support DP 1, 2, 4 lanes Over type C
Video Input Resolution	VESA, maximum 2560×1440
Video input timing	1920×1080,1680×1050 1600x900, 1440x900, 1400×1050,1366×768, 1280×1024,1280×800, 1280×720,1024×768, 1920×1200,1600×1200, 2560×1440 @24 25, 30, 50,60 HZ
Video Output Formats	1 x Wireless
Audio Input Formats	DP 2CH PCM
Audio Output Formats	WIFI 11b/g/n/ac
USB Input	USB type C (USB 2.0 only)
Wireless transmission protocol	WIFI IEEE 802.11 a/g/n/ac
WIFI Frequency band	2.4 GHz & 5 GHz
WIFI Antenna	MIMO 2x2
WIFI Data rate	Up to 1200Mbps

Video Capacity	Wireless Transmission 1080P@ 60Hz, 2560×1440 30Hz
Distance	Typical: 35m without obstacle between WMT3-H and WMS
Latency	< 100ms
Button	Capacitive touch Key and vibration
Indicator	Green/Red/color back-lit LED indicator

MECHANICAL	
Round Unit Dimensions (LxHxR)	without cable: 65mm x 15mm x80mm with cable: L=190mm
Weight	~0.2lbs (-85g)
Surface finish	1-2mm plastic with matte black finish
Power Input	USB Internal 5V
Power Consumption	3W (max.)has context menu
Operation Temperature	- 4 °F to + 113 °F (-20 °C to 45 °C)
Storage Temperature	- 4 °F to + 140°F (- 20 °C to 60 °C)
Relative Humidity	20~ 85% RH (Non-Condensation)

### **APPLICATION EXAMPLE**



LAN Connection Fiber Connection Cooper Cable Audio USB HDMI DisplayPort Control

or Legen

Applications

Conference Rooms, Operating Rooms and Audio-Video Rooms

